

PART NUMBER	HOSE I.D. (INSIDE DIAMETER)	CABLE STRENGTH IN STATIC LOAD	LENGTH LOOP TO LOOP	MAXIMUM PSI FLUID		MAXIMUM PSI FLUID		MAXIMUM PSI FLUID		MAXIMUM PSI FLUID		MAXIMUM PSI FLUID	
				Hose I.D.		Hose I.D.		Hose I.D.		Hose I.D.		Hose I.D.	
CC-3/32	.25" - .75"	675 lbs.	12"	.25"	13,000	.375"	6,000	.5"	3,200	.75"	1,500	1"	800
CC-1/8	.25" - 1"	1,200 lbs.	12"	.25"	20,000	.375"	10,000	.5"	6,000	.75"	2,500	1"	1,500
CC-3/16	.5" - 1.5"	3,200 lbs.	24"	.5"	16,000	.75"	7,000	1"	4,000	1.25"	2,500	1.5"	1,800
CC-1/4	1" - 2"	4,800 lbs.	24"	1"	6,000	1.25"	4,000	1.5"	2,700	2"	1,500	3"	650
CC-5/16	1.5" - 3"	8,800 lbs.	24"	1.5"	4,500	1.75"	3,500	2"	2,500	2.5"	1,700	3"	1,200
CC-3/8	1.5" - 3"	11,000 lbs.	42"	1.5"	6,000	2"	3,000	2.5"	2,000	3"	1,500		
CC-3/8-L	4" - 6"	11,000 lbs.	42"	4"	800	5"	500	6"	400				
CC-7/16	1.5" - 3"	16,000 lbs.	42"	1.5"	9,000	2"	5,000	2.5"	2,500	3"	2,000		
CC-7/16-L	4" - 6"	16,000 lbs.	42"	4"	1,200	5"	800	6"	500				
CC-1/2	3" - 6"	22,000 lbs	42"	3"	3,000	4"	1,800	5"	1,200	6"	800		
CC-1/2-L	8" - 12"	22,000 lbs	42"	8"	400	10"	300	12"	200				

PART NUMBER	HOSE I.D. (INSIDE DIAMETER)	CABLE STRENGTH IN STATIC LOAD	LENGTH LOOP TO LOOP	MAXIMUM PSI AIR		MAXIMUM PSI AIR		MAXIMUM PSI AIR		MAXIMUM PSI AIR		MAXIMUM PSI AIR	
				Hose I.D.		Hose I.D.		Hose I.D.		Hose I.D.		Hose I.D.	
CC-3/32	.25" - .75"	675 lbs.	12"	.25"	6,000	.375"	3,000	.5"	1,600	.75"	750	1"	400
CC-1/8	.25" - 1"	1,200 lbs.	12"	0.25	10,000	0.375	5,000	.5"	3,000	.75"	1,250	1"	750
CC-3/16	.5" - 1.5"	3,200 lbs.	24"	.5"	8,000	.75"	3,500	1"	2,000	1.25"	1,250	1.5"	900
CC-1/4	1" - 2"	4,800 lbs.	24"	1"	5,000	1.25	2,000	1.5"	1,350	2"	750	3"	300
CC-5/16	1.5" - 3"	8,800 lbs.	24"	1.5"	2,200	1.75"	1,750	2"	1,200	2.5"	850	3"	600
CC-3/8	1.5" - 3"	11,000 lbs.	42"	1.5"	3,000	2"	1,500	2.5"	1,000	3"	750		
CC-3/8-L	4" - 6"	11,000 lbs.	42"	4"	400	5"	250	6"	200				
CC-7/16	1.5" - 3"	16,000 lbs.	42"	1.5"	4,500	2"	2,500	2.5"	1,250	3"	1,000		
CC-7/16-L	4" - 6"	16,000 lbs.	42"	4"	600	5"	400	6"	250				
CC-1/2	3" - 6"	22,000 lbs	42"	3"	1,500	4"	900	5"	600	6"	400		
CC-1/2-L	8" - 12"	22,000 lbs	42"	8"	200	10"	150	12"	100				