

Size (in)	Outside Diameter (in)	Wall Thickness (in)	Inside Diameter (in)	Schedule	Temperature (°F)			
					100	200	300	400
					Maximum Pressure (psi)			
1/2"	.840"	.109"	.622"	40	5792 psi	5792 psi	5792 psi	5792 psi
	.840	.147	.546	80	8140	8140	8140	8140
	.840	.188	.464	160	10905	10905	10905	10905
3/4"	1.050	.113	.824	40	4710	4710	4710	4710
	1.050	.154	.742	80	6647	6647	6647	6647
	1.050	.219	.612	160	10014	10014	10014	10014
1"	1.315	.133	1.049	40	4402	4402	4402	4402
	1.315	.179	.957	80	6110	6110	6110	6110
	1.315	.250	.815	160	8969	8969	8969	8969
1-1/4"	1.550	.140	1.380	40	3618	3618	3618	3618
	1.550	.019	1.278	80	5069	5069	5069	5069
	1.550	.250	1.160	160	6849	6849	6849	6849
1-1/2"	1.900	.145	1.610	40	3251	3251	3251	3251
	1.900	.200	1.500	80	4598	4598	4598	4598
	1.900	.281	1.338	160	6710	6710	6710	6710
2"	2.375	.109	2.157	10	1906	1906	1906	1906
	2.375	.154	2.067	40	2736	2736	2736	2736
	2.375	.218	1.939	80	3963	3963	3963	3963
	2.375	.344	1.687	160	6553	6553	6553	6553
2-1/2"	2.875	.120	2.635	10	1727	1727	1727	1727
	2.875	.203	2.469	40	2993	2993	2993	2993
	2.875	.276	2.323	80	4159	4159	4159	4159
	2.875	.375	2.125	160	5825	5825	5825	5825
3"	3.500	.216	3.068	40	2597	2597	2597	2597
	3.500	.300	2.900	80	3681	3681	3681	3681
	3.500	.438	2.624	160	5563	5563	5563	5563
4"	4.500	.237	4.026	40	2199	2199	2199	2199
	4.500	.337	3.826	80	3186	3186	3186	3186
	4.500	.531	3.438	160	5212	5212	5212	5212
5"	5.563	.258	5.047	40	1927	1927	1927	1927
	5.563	.375	4.813	80	2850	2850	2850	2850
	5.563	.625	4.313	160	4938	4938	4938	4938
6"	6.625	.280	6.065	40	1750	1750	1750	1750
	6.625	.432	5.761	80	2752	2752	2752	2752
	6.625	.719	5.187	160	4754	4754	4754	4754